

Technical Specification of CTS-8800

System Model (version)	CTS-8800 (V1.1)
System Type	Portable B/W 4D
Standard Display	10.4 inch LCD
Optional Display	○
TGC	8
Max Frequency	12 MHz
Min Frequency	2.5 MHz
Frequency Variation	5 steps
Scanning Angle Max	180°
Max Depth	252 mm
Probe Socket	2
DICOM 3.0	▲
3D	▲
4D	■
Panoramic Imaging	○
CD-RW/DVD	○
HDD/Storage Capacity	160 G
Body Mark	96
B mode Cineloop Playback	512 frames max
M mode Cineloop Playback	2560 seconds max
Gain Control	0 ~ 100
Focus	1 ~ 4
Scanning Mode	B,2B,4B,M,B/M,ZOOM B,Picture in Picture, 4D/3D
Backlit Keyboard	■
Report Function	■
Growth Chart	■
Standard Transducer	4D probe 4DL40G
Saved Image Format	BMP, JPG
Saved Cineloop Format	CINE, AVI,VOLS
Biopsy Guide Line	▲
Biopsy Guide	▲
Self-defined key	6
One Key Optimization	■
Programmable Preset Function	■
Alphabetic Keypad	■
USB Port	2

Video Out Port	1
Printer Remote Port	1
DC +12V Input Port	○
RJ-45 NIC Port	1
LPT Parallel Printing Port	○
RS-232C Port	○
VGA Port	1
Foot Switch Port	○
S-Video Out Port	○
Lithium Battery	○
Power Adapter	○
Car Charger	○
Rated Power	250VA
CE Mark	■
FDA Clearance	○
Bare Dimension	415*320*310mm
Net Weight	10.5kg
Main Unit Packing Dimension	630*520*430mm
Accessory Packing Dimension	○
Total Gross Weight	17.5kg
Sony UP-897MD Printer	▲
Mitsusbishi P93W Printer	▲
Sony UP-21MD Color Printer	▲

Note:

- Standard configuration included
- ▲ Optional
- Not available or applicable

Last updated: 2009.04.29

For reference only

Subject to change without prior notice